



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/015,926

12/10/2001

Rajeev Krishnamurthi

PA010121

5845

23696

7590

10/18/2006

QUALCOMM INCORPORATED  
5775 MOREHOUSE DR.  
SAN DIEGO, CA 92121

EXAMINER

AHMED, SALMAN

ART UNIT

PAPER NUMBER

2616

DATE MAILED: 10/18/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

<b>Office Action Summary</b>	<b>Application No.</b>		<b>Applicant(s)</b>	
	10/015,926		KRISHNAMURTHI ET AL.	
	<b>Examiner</b>		<b>Art Unit</b>	
	Salman Ahmed		2616	

**-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --**  
**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☐ Responsive to communication(s) filed on \_\_\_\_.
- 2a) ☒ This action is **FINAL**.                      2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-68 is/are pending in the application.  
     4a) Of the above claim(s) \_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-68 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 12/10/2001 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
     Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
     Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).  
     a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- |  |   |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)                                | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. ____. |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                       | 5) <input type="checkbox"/> Notice of Informal Patent Application                       |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)<br>Paper No(s)/Mail Date ____. | 6) <input type="checkbox"/> Other: ____.  |

**DETAILED ACTION**

Claims 1-68 are pending.

Claims 1-68 are rejected.

***Claim Rejections - 35 USC § 102***

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

2. Claims 1, 2, 30 and 32-38 are rejected under 35 U.S.C. 102(e) as being anticipated by Numminen et al. (US PAT 6687499), hereinafter referred to as Numminen.

In regards to claim 1 Numminen anticipates receiving a first message having included therein test settings for one or more channels (column 7 lines 18-20, test mode means that the mobile station to be tested is instructed to maintain a connection on a certain transmission channel) comprising traffic channels, auxiliary channels, (column 11 lines 4-6, data, traffic and control channels) or a combination thereof (column 7 lines 46-47, at first the test equipment sends a comparison and statistical operation start command associated with the data channel); configuring the one or more channels based on the test settings in the first message (column 7 lines 59-61, The mobile station

Art Unit: 2616

closes, i.e. activates, the test loop); receiving test packets via a forward traffic channel (column 8 lines 4-7, once the G loop has been activated the test equipment can start sending test data); transmitting loop back packets via a reverse traffic channel (column 8 lines 39-40, the test equipment receives the uplink frames sent by the mobile station), and transmitting signaling data via traffic or one or more auxiliary channels (column 11 lines 4-6, applicability of the invention to all mobile communication systems in which a mobile station can operate on data, traffic and control channels). Numminen anticipates different modes (column 9 lines 14-15, G Loop and H Loop) of testing are supported, and the testing varies for each one or more channel; and receiving test packets via a forward traffic channel based on the supported mode of testing (column 8 lines 4-6, Once the G loop has been activated the test equipment can start sending test data, i.e. periods of a pseudorandom bit sequence packed in downlink frames).

In regards to claim 30 Numminen anticipates a method for testing one or more channels in a wireless data communication system, comprising: sending a first data transmission (column 8 lines 4-7, test data) via a first channel (column 5 lines 62-63, tests especially the operation of data channels) wherein the first data transmission comprises test packets (column 8 lines 4-7, once the G loop has been activated the test equipment can start sending test data); receiving a second data transmission via a second channel (column 8 lines 39-40, the test equipment receives the uplink frames sent by the mobile station), wherein the second data transmission includes parameter values descriptive of the first data transmission (column 8 lines 30-80, the bit error ratio or frame erasure ratio) and further comprises a

record (column 8 lines 30-80, compiles statistics of the measurement results) for each test packet correctly received; and updating a plurality of variables (column 8 lines 30-80, signal level at which the downlink frames are delivered to the mobile station can be varied) based on the parameter values included in the second data transmission (column 8 lines 30-80, While the G loop is active the mobile station compares the received bit sequence portions to the locally produced portions and measures e.g. the bit error ratio or frame erasure ratio and compiles statistics of the measurement results in a desired manner. Since the received signal is examined in the G loop prior to channel decoding, the locally produced bit sequence at the mobile station also has to be channel encoded for the comparison to be meaningful. Complete statistics or information elements representing the reception error status in general are sent uplink to the test equipment. The test equipment receives the uplink frames sent by the mobile station and demodulates and decrypts them so that the statistical results in the received frame can be processed by the test equipment. The signal level at which the downlink frames are delivered to the mobile station can be varied so that the bit error ratio (BER) detected by it represents the sensitivity of the receiver of the mobile station especially at low signal levels. It is typical of type approval tests that a certain minimum sensitivity is required of the mobile station, which means that at a given signal level the bit error ratio must not exceed a predetermined limit value).

In regards to claims 32 and 33 Numminen anticipates a method for testing the forward link for specific configuration of one or more auxiliary channels (column 11 lines 4-6, data, traffic and control channels) in wireless data communication

system, comprising: receiving a first message having included therein test settings for the one or more auxiliary channels (column 6 lines 54-56, column 6 lines 66-67 and column 7 lines 1-8, the test equipment sends an immediate assignment 503 which may include various instructions for the mobile station. Particularly the immediate assignment 503 contains so-called rest octets in which the first two bits indicate the contents of the rest of the rest octet. By the priority date of this patent application values 11 and 10 of the values of the first two bits of the rest octet have been reserved but values 01 and 00 are unused. In accordance with a preferred embodiment of the invention at least one of these values can be reserved to indicate that in response to the immediate assignment 503 the mobile station to be tested has to set itself in a special test mode); configuring each auxiliary channel based on test settings applicable to the auxiliary channel (column 9 lines 14-15, G Loop and H Loop), wherein the test setting for each channel varies (column 9 lines 14-15, G Loop and H Loop); and transmitting each configured auxiliary channel in accordance with the applicable test settings (column 8 lines 4-6, Once the G loop has been activated the test equipment can start sending test data, i.e. periods of a pseudorandom bit sequence packed in downlink frames).

In regards to claim 2 Numminen anticipates each loop back packet includes data descriptive of one or more test packets (column 8 lines 30-80, While the G loop is active the mobile station compares the received bit sequence portions to the locally produced portions and measures e.g. the bit error ratio or frame erasure ratio and compiles statistics of the measurement results in a desired manner. Since the

received signal is examined in the G loop prior to channel decoding, the locally produced bit sequence at the mobile station also has to be channel encoded for the comparison to be meaningful. Complete statistics or information elements representing the reception error status in general are sent uplink to the test equipment).

In regards to claim 34 Numminen anticipates one or more auxiliary channels is used for signaling (column 11 lines 4-6, data, traffic and control channels and column 6 lines 54-56, the test equipment sends an immediate assignment 503 which may include various instructions for the mobile station).

In regards to claims 35-37 Numminen anticipates the first message includes a first test setting for a particular bit value to be transmitted on an acknowledgment (ACK) channel (column 6 lines 54-56, column 6 lines 66-67 and column 7 lines 1-8, the test equipment sends an immediate assignment 503 which may include various instructions for the mobile station. Particularly the immediate assignment 503 contains so-called rest octets in which the first two bits indicate the contents of the rest of the rest octet. By the priority date of this patent application values 11 and 10 of the values of the first two bits of the rest octet have been reserved but values 01 and 00 are unused. In accordance with a preferred embodiment of the invention at least one of these values can be reserved to indicate that in response to the immediate assignment 503 the mobile station to be tested has to set itself in a special test mode) or the first message includes a second test setting (column 6 lines 54-56, column 6 lines 66-67 and column 7 lines 1-8, the test equipment sends an immediate assignment 503 which may include various instructions for the mobile station. Particularly the immediate assignment 503

contains so-called rest octets in which the first two bits indicate the contents of the rest of the rest octet. By the priority date of this patent application values 11 and 10 of the values of the first two bits of the rest octet have been reserved but values 01 and 00 are unused. In accordance with a preferred embodiment of the invention at least one of these values can be reserved to indicate that in response to the immediate assignment 503 the mobile station to be tested has to set itself in a special test mode) for a particular value to be transmitted on a data rate control (DRC) channel or the first message includes a third test setting (column 6 lines 54-56, column 6 lines 66-67 and column 7 lines 1-8, the test equipment sends an immediate assignment 503 which may include various instructions for the mobile station. Particularly the immediate assignment 503 contains so-called rest octets in which the first two bits indicate the contents of the rest of the rest octet. By the priority date of this patent application values 11 and 10 of the values of the first two bits of the rest octet have been reserved but values 01 and 00 are unused. In accordance with a preferred embodiment of the invention at least one of these values can be reserved to indicate that in response to the immediate assignment 503 the mobile station to be tested has to set itself in a special test mode) for a particular cover to be used for a data rate control (DRC) channel (column 6 lines 20-61).

In regards to claim 38 Numminen anticipates the first message includes a fourth test setting indicative of maintenance of a test mode in event of a connection closure or a lost connection (column 7 lines 18-20, So test mode means that the



mobile station to be tested is instructed to maintain a connection on a certain transmission channel. The mobile station is kept in the test mode by Layer 3 signaling).

***Claim Rejections - 35 USC § 103***

3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

4. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

5. Claims 59 and 60 are rejected under 35 U.S.C. 103(a) as being unpatentable over Numminen in view of Schmutz et al. (US PAT PUB 2002/0028675, hereinafter Schmutz).

In regards to claim 59 Numminen teaches sending a first message having included therein test settings for the traffic channel (column 6 lines 54-56, the test

Art Unit: 2616

equipment sends an immediate assignment 503 which may include various instructions for the mobile station); receiving a plurality of test packets at a plurality of rates (column 9 lines 14-15, G Loop and H Loop) on the traffic channel (column 8 lines 4-6, Once the G loop has been activated the test equipment can start sending test data, i.e. periods of a pseudorandom bit sequence packed in downlink frames); and updating a plurality of variables maintained for the plurality of rates based on the rates of the received test packets variables (column 8 lines 30-80, signal level at which the downlink frames are delivered to the mobile station can be varied) based on the parameter values included in the second data transmission (column 8 lines 30-80, While the G loop is active the mobile station compares the received bit sequence portions to the locally produced portions and measures e.g. the bit error ratio or frame erasure ratio and compiles statistics of the measurement results in a desired manner. Since the received signal is examined in the G loop prior to channel decoding, the locally produced bit sequence at the mobile station also has to be channel encoded for the comparison to be meaningful. Complete statistics or information elements representing the reception error status in general are sent uplink to the test equipment. The test equipment receives the uplink frames sent by the mobile station and demodulates and decrypts them so that the statistical results in the received frame can be processed by the test equipment. The signal level at which the downlink frames are delivered to the mobile station can be varied so that the bit error ratio (BER) detected by it represents the sensitivity of the receiver of the mobile station especially at low signal levels. It is typical of type approval tests that a certain minimum sensitivity is required of the mobile station, which means

that at a given signal level the bit error ratio must not exceed a predetermined limit value).

Numminen does not explicitly teach testing the reverse channel.

Schmutz in the same field of endeavor teaches (page 1 section 0011) in order to accurately test the conditions on the RF channel, the uplink and downlink transmission paths on the link must be tested.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen's system/method by incorporating the steps of testing the reverse channel as taught by Schmutz. The motivation is that (as suggested by Schmutz, page 1 section 0011) in order to accurately test the conditions on the RF channel, the uplink and downlink transmission paths on the link must be tested.

In regards to claim 60 Numminen teaches for each received test packet, updating a first variable based on a sequence number of the test packet (column 8 lines 30-80 and column 8 lines 30-80)

6. Claims 6-8 and 10 are rejected under 35 U.S.C. 103(a) as being unpatentable over Numminen in view of Anderson (US PAT PUB 2005/0003831).

In regards to claim 6, Numminen teaches a method for testing one or more channels in a wireless data communication system, comprising: receiving a first data (column 6 lines 54-56, immediate assignment 503) transmission via a first channel (column 6 lines 54-56, the test equipment sends an immediate assignment 503 which may include various instructions for the mobile station); identifying parameter

Art Unit: 2616

values descriptive of the first data transmission (column 6 lines 66-67 and column 7 lines 1-8, Particularly the immediate assignment 503 contains so-called rest octets in which the first two bits indicate the contents of the rest of the rest octet. By the priority date of this patent application values 11 and 10 of the values of the first two bits of the rest octet have been reserved but values 01 and 00 are unused. In accordance with a preferred embodiment of the invention at least one of these values can be reserved to indicate that in response to the immediate assignment 503 the mobile station to be tested has to set itself in a special test mode); forming a second data transmission with the identified parameter values; and transmitting the second data transmission via a second channel (column 8 lines 37-40, Complete statistics or information elements representing the reception error status in general are sent uplink to the test equipment).

Numminen does not explicitly teach the parameter values comprise at least one of a) a serving sector from which the first data transmission was received, b) a sequence number of the first data transmission, and c) a length of the first data transmission.

Anderson in the same field of endeavor teaches the parameter values comprise length of first data length (page 39, Table 2-6).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen's system/method by incorporating the teaching of immediate assignment message having a message length as taught by Anderson. The motivation is that immediate assignment needs a parameter indicating

the length of the message, so that, the system can easily and efficiently ascertain the total length of the data message it needs to decode.

In regards to claims 7, 8 and 10, Numminen teaches the first channel is a forward traffic (downlink) channel and the second channel is a reverse traffic channel (uplink) (column 2 lines 25-31, test signal is received in the downlink direction, the test signal received is compared with a known form of the test signal, information produced by the comparison about errors detected in the received test signal is stored, and a signal representing the information stored is sent uplink); the first data transmission comprises a plurality of test packets (column 2 lines 25-31, test signal) and the second data transmission comprises a plurality of loop back packets (column 2 lines 25-31, a signal representing the information stored is sent uplink), and wherein the loop back packets include the parameter values descriptive of the test packets (column 8 lines 37-40, Complete statistics or information elements representing the reception error status in general are sent uplink to the test equipment).

7. Claim 5 is rejected under 35 U.S.C. 103(a) as being unpatentable over Numminen in view of Funk et al. (US PAT 6766164), hereinafter referred to as Funk.

In regards to claim 5, Numminen teaches a memory (column 7 line 27, memory media) communicatively coupled to a digital signal processing device (DSPD) (column 7 line 26, a microprocessor) capable of interpreting digital information to: receive a first message having included therein test settings for one or more channels (column 7 lines 18-20, test mode means that the mobile station to be tested is instructed to maintain a

Art Unit: 2616

connection on a certain transmission channel) comprising traffic channels, auxiliary channels, (column 11 lines 4-6, data, traffic and control channels) or a combination thereof (column 7 lines 46-47, at first the test equipment sends a comparison and statistical operation start command associated with the data channel); configure the one or more channels based on the test settings in the first message (column 7 lines 59-61, The mobile station closes, i.e. activates, the test loop); receive test packets via a forward traffic channel (column 8 lines 4-7, once the G loop has been activated the test equipment can start sending test data); transmit a plurality of loop back packets via a reverse traffic channel (column 8 lines 39-40, the test equipment receives the uplink frames sent by the mobile station), and transmit a plurality of loop back packets via a reverse traffic channel and transmitting signaling data via traffic or one or more auxiliary channels (column 11 lines 4-6, applicability of the invention to all mobile communication systems in which a mobile station can operate on data, traffic and control channels). Numminen teaches different modes (column 9 lines 14-15, G Loop and H Loop) of testing are supported, and the testing varies for each one or more channel; and receiving test packets via a forward traffic channel based on the supported mode of testing (column 8 lines 4-6, Once the G loop has been activated the test equipment can start sending test data, i.e. periods of a pseudorandom bit sequence packed in downlink frames).

Numminen does not explicitly teach one loop back packet is formed for each particular time interval.

Funk in the same field of endeavor teaches (Column 3 lines 61-67) test packets being formed for particular time interval.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen's method by incorporating one loop back packet being formed for each particular time interval as taught by Funk. The motivation is that generating and sending test packets at regular interval helps to diagnose a communication system very efficiently and effectively.

8. Claim 9 is rejected under 35 U.S.C. 103(a) as being unpatentable over Numminen and Anderson as applied to claim 6 above and further in view of Funk.

In regards to claim 9, Numminen and Anderson teach sending loopback packet as described in the rejections of claim 6 above.

Numminen and Anderson do not explicitly teach one loop back packet is formed for each particular time interval.

Funk in the same field of endeavor teaches (Column 3 lines 61-67) test packets being formed for particular time interval.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen and Anderson's method by incorporating one loop back packet being formed for each particular time interval as taught by Funk. The motivation is that generating and sending test packets at regular interval helps to diagnose a communication system very efficiently and effectively.

Art Unit: 2616

9. Claim 24 is rejected under 35 U.S.C. 103(a) as being unpatentable over Numminen and Anderson as applied to claim 6 above and further in view of Buchholz et al. (US PAT 5555266), hereinafter referred to as Buchholz.

In regards to claim 24, Numminen and Anderson teach loopback packets as described in the rejections of claim 6 above.

Numminen and Anderson do not explicitly teach each packet on the second data transmission includes a parameter value indicative of omission of one or more packets received on the first data transmission.

Buchholz in the same field of endeavor teaches in response to the receipt of a data packet (310) from a remote unit (112), the communications controller (110) identifies missing data within the data packet transmission, determines whether communication resources are available to support retransmission of the missing data, and if so, transmits a response to the requesting remote unit identifying the missing data.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen and Anderson's system by incorporating the method of notifying sender about missing data as taught by Buchholz. The motivation is that such method will accurately notify the sender about any problems in the communication link, which results in loss of packets; thus making the network more reliable.



Art Unit: 2616

10. Claim 28 is rejected under 35 U.S.C. 103(a) as being unpatentable over Numminen in view of Buchholz et al. (US PAT 5555266), hereinafter referred to as Buchholz, and further in view of Anderson.

In regards to claim 28, Numminen teaches a memory (column 7 line 27, memory media) communicatively coupled to a digital signal processing device (DSPD) (column 7 line 26, a microprocessor) capable of interpreting digital information to: receive a first data transmission via a first channel wherein first data transmission comprises a plurality of packets (column 7 lines 18-20, test mode means that the mobile station to be tested is instructed to maintain a connection on a certain transmission channel); identifying parameter values descriptive of the first data transmission (column 7 lines 46-47, at first the test equipment sends a comparison and statistical operation start command associated with the data channel); form a second data transmission with the identical parameter values (column 7 lines 59-61, The mobile station closes, i.e. activates, the test loop); transmit the second data transmission via a second channel (column 8 lines 39-40, the test equipment receives the uplink frames sent by the mobile station).

Numminen does not explicitly teach each packet on the second data transmission includes a parameter value indicative of omission of one or more packets received on the first data transmission.

Buchholz in the same field of endeavor teaches in response to the receipt of a data packet (310) from a remote unit (112), the communications controller (110) identifies missing data within the data packet transmission, determines whether

Art Unit: 2616

communication resources are available to support retransmission of the missing data, and if so, transmits a response to the requesting remote unit identifying the missing data.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen's system by incorporating the method of notifying sender about missing data as taught by Buchholz. The motivation is that such method will accurately notify the sender about any problems in the communication link, which results in loss of packets; thus making the network more reliable.

Numminen and Buchholz do not explicitly teach the parameter values comprise at least one of a) a serving sector from which the first data transmission was received, b) a sequence number of the first data transmission, and c) a length of the first data transmission.

Anderson in the same field of endeavor teaches the parameter values comprise length of first data length (page 39, Table 2-6).

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen and Buchholz's system/method by incorporating the teaching of immediate assignment message having a message length as taught by Anderson. The motivation is that immediate assignment needs a parameter indicating the length of the message, so that, the system can easily and efficiently ascertain the total length of the data message it needs to decode.

11. Claims 29, 31, 39, 45, 46, 47, 48, 50-58, 61-63, 65, 67 and 68 are rejected under 35 U.S.C. 103(a) as being unpatentable over Numminen, in view of Kobayasi et al. (US PAT 6333932), hereinafter referred to as Kobayasi, and Ikeda (US PAT 5636212).

In regards to claims 29, 31, 39, 45, 57, 63, 67 and 68 Numminen teaches a method for testing one or more channels in a wireless data communication system, comprising: receiving a plurality of test packets via a forward traffic channel as described in the rejections of claim 1 above.

Numminen does not explicitly teach identifying a transmission source and a sequence number of each received test packet; forming a plurality of loop back packets for the plurality of received test packets, wherein each loop back packet covers zero or more test packets and includes the transmission source and the sequence number of each covered test packet; and transmitting the loop back packets. In regards to claim 45, Numminen does not explicitly teach selecting rates for the test packets based on a rate selection scheme, and transmitting the test packets at the selected rates on the traffic channel. In regards to claims 50-52, 54 and 55 Numminen does not explicitly teach of having protocol type, packet type, number of records field, time interval, source address, sequence number in the test packet. In regards to claim 58, 62 and 65 Numminen does not explicitly teach a queue for the test packets.

Kobayasi in the same field of endeavor teaches, (column 2 lines 55-67) a test being started by issuing a test connectionless packet transmission request message (test start request) from the OS center 1 to SW station 3. The request message contains an identification information ID indicating terminal SW station 6. SW station 3

generates a test packet with the identification address of terminal SW station 6 set as its destination address DA and the identification address of its home station (SW station 3) set as its source address SA. The test packet is output to terminal SW station 6. In SW stations 4 and 5, test packets are processed as normal packets and transferred to terminal SW station 6. On receipt of the test packet, terminal SW station 6 outputs the packet with its DA and SA inverted. That is, the packet is returned from terminal SW station 6 to SW station 3, and it is reported to the OS center 1 upon re-arrival of the packet at the source SW station 3. Kobayasi further teaches the L2-PDU shown in FIG. 783 is an example of a BOM cell. The 2 bytes preceded by the header field stores a segment type ST, sequence number SN, and message identifier MID (or a multiplex identifier). The sequence number SN is a serial number assigned to a transferred cell for convenience in detecting the cell if it is lost or mistakenly inserted. In regards to claim 45 Kobayasi teaches (column 97 lines 45-46) Loopback of a test cell is done in a 156 Mbps cell highway. In regards to claims 50, 51, 54 and 55 Kobayasi discloses protocol type, packet type, number of records field, time interval, source address, sequence number in the packets shown in FIGS. 582 through 628. In regards to claim 52 Kobayasi teaches (column 3 lines 5-10) that since the source SW station 3 and the terminal SW station 6 mark the time stamp onto the payload field of the packet, the OS center 1 is informed of the transmission time of packets according to the information. In regards to claim 58, 62 and 65 Kobayasi teaches buffers (fig 132) for data packets.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen's teaching by incorporating the loopback test

Art Unit: 2616

scheme as taught by Kobayasi. The motivation is that (as suggested by Kobayasi column 317 lines 29-34) the present invention realizes an efficient test within a short time by performing a test cell loopback check, which has been made in a test device, through a test program in the switch. Additionally, transmitting cell data from a test device requires no testing units because the loopback jig can replace the testing units. Further motivation (as suggested by Numminen, column 11 lines 5-8) is that the invention can also be modified in many ways without departing from the scope of the invention defined by the claims.

In regards to claim 53, Numminen does not explicitly teach field indicative of whether any loop back packets were lost due to buffer overflow.

Kobayasi in the same field of endeavor teaches, (column 2 lines 55-67) a test being started by issuing a test connectionless packet transmission request message (test start request) from the OS center 1 to SW station 3. The request message contains an identification information ID indicating terminal SW station 6. SW station 3 generates a test packet with the identification address of terminal SW station 6 set as its destination address DA and the identification address of its home station (SW station 3) set as its source address SA. The test packet is output to terminal SW station 6. In SW stations 4 and 5, test packets are processed as normal packets and transferred to terminal SW station 6. On receipt of the test packet, terminal SW station 6 outputs the packet with its DA and SA inverted. That is, the packet is returned from terminal SW station 6 to SW station 3, and it is reported to the OS center 1 upon re-arrival of the packet at the source SW station 3. Kobayasi further teaches the L2-PDU shown in FIG.

783 is an example of a BOM cell. The 2 bytes preceded by the header field stores a segment type ST, sequence number SN, and message identifier MID (or a multiplex identifier). The sequence number SN is a serial number assigned to a transferred cell for convenience in detecting the cell if it is lost or mistakenly inserted.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen's system/method by incorporating the steps of having source id and sequence number in test packets as taught by Kobayasi. The motivation is that having a source and sequence number enables a system to easily and efficiently identify the source of the test packets and number of packets received or lost due to overflow for statistical record keeping.

In regards to claims 46, 47 and 57 Numminen and Kobayasi do not explicitly teach message having maximum and minimum rate for rate selection.

Ikeda in the same field of endeavor teaches (column 8 lines 38-39) reservation request being issued with a maximum band-width and a minimum band-width.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen and Kobayasi's system/method by incorporating the concept of sending maximum band-width and a minimum band-width via message as taught by Ikeda. The motivation is that (as suggested by Ikeda, column 2 lines 5-10) to provide a flexible method of reserving a band-width for a burst capable of flexibly reserving a band-width according to a maximum band-width and a minimum band-width requested for reservation.

In regards to claim 48, Numminen and Kobayasi do not explicitly teach with the steps of the selected rates for the test packets being further limited by a maximum rate specified by a media access control (MAC) protocol

In regards to claim 48 it would have been obvious of one of ordinary skill in the art at the time of invention to modify Numminen and Kobayasi's system/method with the steps of the selected rates for the test packets being further limited by a maximum rate specified by a media access control (MAC) protocol; as a link defined to have a maximum bandwidth rate cannot operate in a higher bandwidth which may cause overflow of data in buffers and in result cause loss of packets.

In regards to claim 57, Numminen and Kobayasi do not explicitly teach testing the reverse channel.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen and Kobayasi's system/method by incorporating the steps of testing the reverse channel. The motivation is that in order to accurately test the conditions on the RF channel, the uplink and downlink transmission paths on the link must be tested.

In regards to claim 31, Numminen teaches updating a plurality of variables based on the transmission source and sequence number of each packets included in the second data transmission (column 10 lines 46-49, the quality control station of a cellular radio network may collect statistical data sent by mobile stations and received by base stations from different parts of the cellular radio network).

In regards to claims 39 and 56 Numminen teaches a memory (column 7 line 27, memory media) communicatively coupled to a digital signal-processing device (DSPD) (column 7 line 26, a microprocessor).

In regards to claim 49 Numminen teaches the first message includes an indication of maintenance of a test mode on the traffic channel in event of a connection closure or a lost connection (column 7 lines 18-20, So test mode means that the mobile station to be tested is instructed to maintain a connection on a certain transmission channel. The mobile station is kept in the test mode by Layer 3 signaling).

In regards to claims 61 and 67 Numminen teaches a receive data processor (figure 3 element 304), a transmit data processor (figure 3 element 310) and a controller (figure 3 element 307).

12. Claims 11-13, 15-20, 22, 23, 25-27 are rejected under 35 U.S.C. 103(a) as being unpatentable over Numminen, Anderson as applied to claim 6 above and further in view of Kobayasi and Ikeda.

In regards to claims 11, 12, 13, 15, 16, 17, 18, 19, 20, 22, 23, 25, 26 and 27 Numminen and Anderson teach a method for testing one or more channels in a wireless data communication system, comprising: receiving a plurality of test packets via a forward traffic channel as described in the rejections of claim 6 above.

Numminen and Anderson do not explicitly teach of having protocol type, packet type, number of records field, time interval, source address, sequence number in the test packet.



Kobayasi in the same field of endeavor teaches protocol type, packet type, number of records field, time interval, source address, sequence number in the packets shown in FIGS. 582 through 628. In regards to claims 13 and 20 Kobayasi teaches (column 3 lines 5-10) that since the source SW station 3 and the terminal SW station 6 mark the time stamp onto the payload field of the packet, the OS center 1 is informed of the transmission time of packets according to the information.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen and Anderson's system/method by incorporating the loopback test scheme as taught by Kobayasi. The motivation is that (as suggested by Kobayasi column 317 lines 29-34) the present invention realizes an efficient test within a short time by performing a test cell loopback check, which has been made in a test device, through a test program in the switch. Additionally, transmitting cell data from a test device requires no testing units because the loopback jig can replace the testing units. Further motivation (as suggested by Numminen, column 11 lines 5-8) is that the invention can also be modified in many ways without departing from the scope of the invention defined by the claims.

13. Claims 40-43 and 44 are rejected under 35 U.S.C. 103(a) as being unpatentable over Numminen in view of Oommen et al. (US PAT 6799203).

In regards to claims 40-43 and 44 Numminen teaches a method for testing one or more channels in a wireless data communication system, comprising: receiving a plurality of test packets via a forward traffic channel as described in the rejections of

claim 1 above. In regards to claims 40, 41, 42 and 43 Numminen teaches a method of collecting data for a first parameter while in idle state (column 7 lines 46-59, at first the test equipment sends a comparison and statistical operation start command associated with the data channel, which command can be called CLOSE\_Multi-slot\_loop\_CMD. The close command may include an identifier on the basis of which the mobile station identifies the G loop. The mobile station acknowledges the message using an acknowledge message which can be called CLOSE\_Multi-slot\_loop\_ACK. The mobile station closes, i.e. activates, the test loop in a certain time after it has sent the acknowledge. . Numminen teaches collecting a second statistic for a second parameter while in connected state (column 8 lines 4-6, once the G loop has been activated the test equipment can start sending test data, i.e. periods of a pseudorandom bit sequence packed in downlink frames). Numminen teaches receiving a first message requesting the first or second statistic, and sending a second message with the requested first or second statistic (column 8 lines 29-39, while the G loop is active the mobile station compares the received bit sequence portions to the locally produced portions and measures e.g. the bit error ratio or frame erasure ratio and compiles statistics of the measurement results in a desired manner. Complete statistics or information elements representing the reception error status in general are sent uplink to the test equipment).

In regards to claim 40, 41, 42 and 43 Numminen does not explicitly teach, collecting statistics during each of the transactions.

Oommen in the same field of endeavor teaches (column 2 lines 46-49) OTAMD involves requesting statistics and performing diagnostic tests in the MS using a command issued from the network for testing purpose.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen's teaching by incorporating the statistic gathering during transactions as taught by Oommen. The motivation is that (as taught by Oommen, column 1 lines 14-15) a fast and efficient method for activating and managing a MS over the air would be beneficial both for the user and the wireless service provider.

In regards to claim 44, Numminen teaches a memory (column 7 line 27, memory media) communicatively coupled to a digital signal processing device (DSPD) (column 7 line 26, a microprocessor).

14. Claims 64 and 66 are rejected under 35 U.S.C. 103(a) as being unpatentable over Numminen, Kobayasi and Ikeda.

In regards to claims 64 and 66 Numminen teaches a method/means for testing one or more channels in a wireless data communication system, comprising: receiving a plurality of test packets via a forward traffic channel as described in the rejections of claim 1 above. In regards to claim 66 Numminen teaches a method of collecting data for a first parameter while in idle state (column 7 lines 46-59, at first the test equipment sends a comparison and statistical operation start command associated with the data channel, which command can be called CLOSE\_Multi-slot\_loop\_CMD. The close

Art Unit: 2616

command may include an identifier on the basis of which the mobile station identifies the G loop. The mobile station acknowledges the message using an acknowledge message which can be called CLOSE\_Multi-slot\_loop\_ACK. The mobile station closes, i.e. activates, the test loop in a certain time after it has sent the acknowledge. Numminen teaches collecting a second statistic for a second parameter while in connected state (column 8 lines 4-6, once the G loop has been activated the test equipment can start sending test data, i.e. periods of a pseudorandom bit sequence packed in downlink frames). Numminen teaches receiving a first message requesting the first or second statistic, and sending a second message with the requested first or second statistic (column 8 lines 29-39, while the G loop is active the mobile station compares the received bit sequence portions to the locally produced portions and measures e.g. the bit error ratio or frame erasure ratio and compiles statistics of the measurement results in a desired manner. Complete statistics or information elements representing the reception error status in general are sent uplink to the test equipment).

Numminen does not explicitly teach test packets having transmission source and a sequence number.

Kobayasi in the same field of endeavor teaches, (column 2 lines 55-67) a test being started by issuing a test connectionless packet transmission request message (test start request) from the OS center 1 to SW station 3. The request message contains an identification information ID indicating terminal SW station 6. SW station 3 generates a test packet with the identification address of terminal SW station 6 set as its destination address DA and the identification address of its home station (SW station 3)

set as its source address SA. The test packet is output to terminal SW station 6. In SW stations 4 and 5, test packets are processed as normal packets and transferred to terminal SW station 6. On receipt of the test packet, terminal SW station 6 outputs the packet with its DA and SA inverted. That is, the packet is returned from terminal SW station 6 to SW station 3, and it is reported to the OS center 1 upon re-arrival of the packet at the source SW station 3. Kobayasi further teaches the L2-PDU shown in FIG. 783 is an example of a BOM cell. The 2 bytes preceded by the header field stores a segment type ST, sequence number SN, and message identifier MID (or a multiplex identifier). The sequence number SN is a serial number assigned to a transferred cell for convenience in detecting the cell if it is lost or mistakenly inserted.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen's system/method by incorporating the steps of having source id and sequence number in test packets as taught by Kobayasi. The motivation is that having a source and sequence number enables a system to easily and efficiently identify the source of the test packets and number of packets received for statistical record keeping.

Numminen and Kobayasi does not explicitly teach message having maximum and minimum rate for rate selection

Ikeda in the same field of endeavor teaches (column 8 lines 38-39) reservation request being issued with a maximum band-width and a minimum band-width.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen and Kobayasi's system/method by

incorporating the concept of sending maximum band-width and a minimum band-width via message as taught by Ikeda. The motivation is that (as suggested by Ikeda, column 2 lines 5-10) to provide a flexible method of reserving a band-width for a burst capable of flexibly reserving a band-width according to a maximum band-width and a minimum band-width requested for reservation.

In regards to claim 64 Numminen teaches a receive data processor (figure 3 element 304), a transmit data processor (figure 3 element 310) and a controller (figure 3 element 307).

15. Claims 14 and 21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Numminen, Anderson as applied to claim 6 above and further in view of Kobayasi.

Numminen and Anderson teach a method for testing one or more channels in a wireless data communication system, comprising: receiving a plurality of test packets via a forward traffic channel as described in the rejections of claim 6 above.

Numminen and Anderson do not explicitly teach field indicative of whether any loop back packets were lost due to buffer overflow and a field indicative of a number of MAC packets received in a Physical Layer packet containing the test packet covered by the record.

Kobayasi in the same field of endeavor teaches, (column 2 lines 55-67) a test being started by issuing a test connectionless packet transmission request message (test start request) from the OS center 1 to SW station 3. The request message contains an identification information ID indicating terminal SW station 6. SW station 3

generates a test packet with the identification address of terminal SW station 6 set as its destination address DA and the identification address of its home station (SW station 3) set as its source address SA. The test packet is output to terminal SW station 6. In SW stations 4 and 5, test packets are processed as normal packets and transferred to terminal SW station 6. On receipt of the test packet, terminal SW station 6 outputs the packet with its DA and SA inverted. That is, the packet is returned from terminal SW station 6 to SW station 3, and it is reported to the OS center 1 upon re-arrival of the packet at the source SW station 3. Kobayasi further teaches the L2-PDU shown in FIG. 783 is an example of a BOM cell. The 2 bytes preceded by the header field stores a segment type ST, sequence number SN, and message identifier MID (or a multiplex identifier). The sequence number SN is a serial number assigned to a transferred cell for convenience in detecting the cell if it is lost or mistakenly inserted.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify Numminen's system/method by incorporating the steps of having source id and sequence number in test packets as taught by Kobayasi. The motivation is that having a source and sequence number enables a system to easily and efficiently identify the source of the test packets and number of packets received or lost due to overflow for statistical record keeping.

### ***Response to Arguments***

16. Applicant's arguments, see pages 17-23 of the Remarks section, filed 9/25/2006, with respect to the rejections of the claims have been fully considered and are not persuasive.

In regards to claims 1, 5, 29, 31, 39, 61, 63, 67 and 68 the Applicant argues that (see page 18 Paragraph one and two, page 19 paragraph 5, page 20 paragraph one and two, page 21 paragraph two) Numminen reference does not teach the newly amended claim with limitation "A method for testing a plurality of channels..., wherein different modes of testing are supported, and the testing varies for each one or more channel" and further "receiving test packets via a forward traffic channel based on the supported mode of testing". However Examiner respectfully disagrees with this assertion. Numminen reference does teach the cited limitations. Numminen reference teaches different modes (column 9 lines 14-15, G Loop and H Loop) of testing being supported, and the testing varies for each one or more channel; and receiving test packets via a forward traffic channel based on the supported mode of testing (column 8 lines 4-6, Once the G loop has been activated the test equipment can start sending test data, i.e. periods of a pseudorandom bit sequence packed in downlink frames).

In regards to claims 6, 9, 11-13, 15-20, 22-28 the Applicant argues that (see page 18 Paragraph three, page 19 paragraph 5 and 6, page 21 paragraph three) Numminen reference does not teach the newly amended claim with limitation "the parameter values comprise at least one of a) a serving sector from which the first data transmission was received, b) a sequence number of the first data transmission, and c) a length of the first data transmission. However, Applicant's amendment of the claim



necessitated a new ground of rejection presented in this office action. As such further response to Applicant's argument to claim 6 is moot.

In regards to claim 30, the Applicant argues that (see page 18 paragraph four) Numminen reference does not teach the newly amended claim with limitation "sending a first data transmission via a first channel, wherein the first data transmission comprises test packets" and "receiving a second data transmission via a second channel, wherein the second data transmission includes parameter values descriptive of the first data transmission and further comprises a record for each test packet correctly received." However, Examiner respectfully disagrees with the assertion. Numminen reference does teach the limitations. Numminen reference teaches a method for testing one or more channels in a wireless data communication system, comprising: sending a first data transmission (column 8 lines 4-7, test data) via a first channel (column 5 lines 62-63, tests especially the operation of data channels) wherein the first data transmission comprises test packets (column 8 lines 4-7, once the G loop has been activated the test equipment can start sending test data); receiving a second data transmission via a second channel (column 8 lines 39-40, the test equipment receives the uplink frames sent by the mobile station), wherein the second data transmission includes parameter values descriptive of the first data transmission (column 8 lines 30-80, the bit error ratio or frame erasure ratio) and further comprises a record (column 8 lines 30-80, compiles statistics of the measurement results) for each test packet correctly received; and updating a plurality of variables (column 8 lines 30-80, signal level at which the downlink frames are delivered

to the mobile station can be varied) based on the parameter values included in the second data transmission (column 8 lines 30-80, While the G loop is active the mobile station compares the received bit sequence portions to the locally produced portions and measures e.g. the bit error ratio or frame erasure ratio and compiles statistics of the measurement results in a desired manner. Since the received signal is examined in the G loop prior to channel decoding, the locally produced bit sequence at the mobile station also has to be channel encoded for the comparison to be meaningful. Complete statistics or information elements representing the reception error status in general are sent uplink to the test equipment. The test equipment receives the uplink frames sent by the mobile station and demodulates and decrypts them so that the statistical results in the received frame can be processed by the test equipment. The signal level at which the downlink frames are delivered to the mobile station can be varied so that the bit error ratio (BER) detected by it represents the sensitivity of the receiver of the mobile station especially at low signal levels. It is typical of type approval tests that a certain minimum sensitivity is required of the mobile station, which means that at a given signal level the bit error ratio must not exceed a predetermined limit value).

In regards to claim 32, the Applicant argues that (see page 19 paragraph two) Numminen reference does not teach "configuring each auxiliary channel based on test settings applicable to the auxiliary channel, wherein the test setting for each channel varies". However, Examiner respectfully disagrees with the assertion. Numminen reference does teach the limitations. Numminen reference teaches configuring each auxiliary channel based on test settings applicable to the

Art Unit: 2616

auxiliary channel (column 9 lines 14-15, G Loop and H Loop), wherein the test setting for each channel varies (column 9 lines 14-15, G Loop and H Loop); and transmitting each configured auxiliary channel in accordance with the applicable test settings (column 8 lines 4-6, Once the G loop has been activated the test equipment can start sending test data, i.e. periods of a pseudorandom bit sequence packed in downlink frames).

In regards to claim 59, the Applicant argues that (see page 19 paragraph three) Numminen reference does not teach "receiving a plurality of test packets at a plurality of rates on the reverse traffic channel" and "updating a plurality of variables maintained for the plurality of rates based on the rates of the received test packets." However, Examiner respectfully disagrees with the assertion. Numminen reference does teach the limitations. Numminen reference teaches receiving a plurality of test packets at a plurality of rates (column 9 lines 14-15, G Loop and H Loop) on the traffic channel (column 8 lines 4-6, Once the G loop has been activated the test equipment can start sending test data, i.e. periods of a pseudorandom bit sequence packed in downlink frames); and updating a plurality of variables maintained for the plurality of rates based on the rates of the received test packets variables (column 8 lines 30-80, signal level at which the downlink frames are delivered to the mobile station can be varied) based on the parameter values included in the second data transmission (column 8 lines 30-80, While the G loop is active the mobile station compares the received bit sequence portions to the locally produced portions and measures e.g. the bit error ratio or frame erasure ratio and compiles statistics of the measurement results in a desired manner.

Since the received signal is examined in the G loop prior to channel decoding, the locally produced bit sequence at the mobile station also has to be channel encoded for the comparison to be meaningful. Complete statistics or information elements representing the reception error status in general are sent uplink to the test equipment. The test equipment receives the uplink frames sent by the mobile station and demodulates and decrypts them so that the statistical results in the received frame can be processed by the test equipment. The signal level at which the downlink frames are delivered to the mobile station can be varied so that the bit error ratio (BER) detected by it represents the sensitivity of the receiver of the mobile station especially at low signal levels. It is typical of type approval tests that a certain minimum sensitivity is required of the mobile station, which means that at a given signal level the bit error ratio must not exceed a predetermined limit value).

In regards to claims 45, 46 and 56 the Applicant argues that (see page 20 paragraph three and four) Numminen reference does not teach "selecting rates for the test packets based on a rate selection scheme, and transmitting the test packets at the selected rates on the traffic channel". However, Examiner respectfully disagrees with the assertion. Numminen reference does teach the limitations. Numminen reference teaches (column 97 lines 45-46) Loopback of a test cell is done in a 156 Mbps cell highway. It is inherent that in order to select a rate, there is a mechanism (software and/or hardware) in place to select such rate.

In regards to claims 57 and 58 the Applicant argues that (see page 21 paragraph

one) Numminen reference and Ikeda do not teach a minimum rate and a maximum rate ...on the reverse traffic channel. Applicant's amendment of the claim 57 in view of updated search necessitated a new ground of rejection presented in this office action. As such further response to Applicant's argument to claim 6 is moot.

In regards to claims 40 the Applicant argues that (see page 21 paragraph five) Numminen and Oommen reference do not teach the newly amended claim limitation "collecting a first statistic for a first parameter while in an Idle State" and "collecting a second statistic for a second parameter while in a Connected State." However, Examiner respectfully disagrees with the assertion. The present claim language is broad and in view of the broadest reasonable interpretation of the claim language, the Numminen and Oommen do teach the cited limitations. Numminen teaches a method of collecting data for a first parameter while in idle state (column 7 lines 46-59, at first the test equipment sends a comparison and statistical operation start command associated with the data channel, which command can be called CLOSE\_Multi-slot\_loop\_CMD. The close command may include an identifier on the basis of which the mobile station identifies the G loop. The mobile station acknowledges the message using an acknowledge message which can be called CLOSE\_Multi-slot\_loop\_ACK. The mobile station closes, i.e. activates, the test loop in a certain time after it has sent the acknowledge. . Numminen teaches collecting a second statistic for a second parameter while in connected state (column 8 lines 4-6, once the G loop has been activated the test equipment can start sending test data, i.e. periods of a pseudorandom bit sequence packed in downlink frames).

In regards to claims 64 the Applicant argues that (see page 21 last paragraph) Numminen reference do not teach "a receive data processor operative to receive a first message having included therein a minimum rate and a maximum rate for data transmission on a reverse traffic channel" as claimed in claim 1. Applicant argues further, Numminen fails to disclose "each test packet includes a sequence number of a test packet last transmitted at each of a plurality of possible rates, and to select rates for the test packets based on a rate selection scheme and limited by the minimum and maximum rates." However, Examiner respectfully disagrees with the assertion. Numminen in view of Kobayasi reference do teach the limitations. Numminen and Kobayasi teach a method for testing one or more channels in a wireless data communication system, comprising: receiving a plurality of test packets via a forward traffic channel as described in the rejections of claim 1 above. Kobayasi in the same field of endeavor teaches, (column 2 lines 55-67) a test being started by issuing a test connectionless packet transmission request message (test start request) from the OS center 1 to SW station 3. The request message contains an identification information ID indicating terminal SW station 6. SW station 3 generates a test packet with the identification address of terminal SW station 6 set as its destination address DA and the identification address of its home station (SW station 3) set as its source address SA. The test packet is output to terminal SW station 6. In SW stations 4 and 5, test packets are processed as normal packets and transferred to terminal SW station 6. On receipt of the test packet, terminal SW station 6 outputs the packet with its DA and SA inverted. That is, the packet is returned from terminal SW station 6 to SW station 3, and it is

reported to the OS center 1 upon re-arrival of the packet at the source SW station 3. Kobayasi further teaches the L2-PDU shown in FIG. 783 is an example of a BOM cell. The 2 bytes preceded by the header field stores a segment type ST, sequence number SN, and message identifier MID (or a multiplex identifier). The sequence number SN is a serial number assigned to a transferred cell for convenience in detecting the cell if it is lost or mistakenly inserted. Numminen also teaches a receive data processor (figure 3 element 304), a transmit data processor (figure 3 element 310) and a controller (figure 3 element 307).

In regards to claims 66 the Applicant argues that (see page 22 first paragraph) Numminen reference do not teach "means for receiving a first message having included therein a minimum rate and a maximum rate for data transmission on a reverse traffic channel." Further, "means for selecting rates for the test packets based on a rate selection scheme and limited by the minimum and maximum rates". However, Examiner respectfully disagrees with the assertion. Numminen, Kobayasi and Ikeda reference do teach the limitations. Numminen, Kobayasi and Ikeda reference teach (column 8 lines 38-39) reservation request being issued with a maximum band-width and a minimum band-width.

Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

### ***Conclusion***

17. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Salman Ahmed whose telephone number is (571)272-8307. The examiner can normally be reached on 8:30 am - 5:00 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Hassan Kizou can be reached on (571) 272-3088. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.




Art Unit: 2616

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Art Unit 2616

SA  
10/4/2006



HASSAN KIZOU  
SUPERVISORY PATENT EXAMINER  
TECHNOLOGY CENTER 2600